



Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Dyna-Plex 21C Aldura EP

Grease
Heavy Duty Petroleum Lubricant
Product Code: G300

Universal Lubricants, A PetroChoice Company
2824 N Ohio Street
Wichita, Kansas 67219
Website: www.universallubes.com

1-800-444-6457 Telephone
1-316-832-3627 Product Information telephone
1-800-424-9300 US, Canada, Puerto Rico, Virgin Isl.- Emergency telephone (CHEMTREC)
+1-703-527-3887 International / Maritime Emergency telephone (CHEMTREC)

2. HAZARDS IDENTIFICATION

OSHA/HCS Status:

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of this product.

Physical Hazards: Not classified

Health Hazards: Not Classified

Environmental Hazards: Not classified

Signal Word: No signal word

Hazard Statement: No known significant effects or critical hazards.

GHS Symbol: *No Symbol*

Precautionary Statements

General:	Read label before use. Keep out of reach of children. If medical advice is needed, have product information at hand.
Prevention:	Not applicable
Response:	Not applicable
Storage:	Not applicable
Disposal:	Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms: Heavy Duty Petroleum Lubricant, Grease

Formula: Mixture

Molecular Weight: Variable

Component	CAS Number	Concentration %
Base Lubricating Oils Mixture		75-85
Additive Package	Trade Secret	10-15
Polyurea Thickener	Trade Secret	5-10

4. FIRST AID MEASURES

Eyes

Immediately flush eyes with large amounts of fresh water and continue flushing until irritation subsides. Seek medical attention.

Inhalation

If breathing difficulty exists, remove individual away from exposure and into fresh air. Seek medical attention.

Skin

Remove contaminated clothing. Wash contaminated area repeatedly with soap and water. Seek medical attention for persistent irritation.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

5. FIREFIGHTING MEASURES

Suitable extinguishing media

Use dry chemical, foam, carbon dioxide (CO₂) or water spray or water fog.

Specific hazards from combustion

Carbon monoxide, carbon dioxide and other oxides may be generated as products of combustion.

Special protective equipment for fire-fighters

Wear full firefighting turn-out gear (full bunker gear), and respiratory protection (SCBA). Cool fire exposed containers with water spray and avoid spreading burning material with water used for cooling purposes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions and Protective equipment

Personal Protection, see section 8. Any individual not wearing protective equipment should not enter spill or contaminated area until all clean-up has been completed.

Emergency procedures

For personal emergency procedures see section 4. For fire emergency procedures see section 5. Contain spilled oil liquid if possible without posing any risk or personal injury.

Environmental precautions

Prevent spreading over a wide area. Contain spill immediately. Contact appropriate authorities of spill. Do not allow spill to enter sewer system, drains of any kind, surface water or water courses. Avoid flushing to such areas as well.

Methods and materials for containment and cleaning up

Soak up or absorb with appropriate inert materials such as, sand, clay, silica gel, acid binder, universal binder, sawdust, paper fiber etc. Large spills may be picked up using vacuum pumps, shovels, buckets or other means of transfer and place into drums or any other approved and suitable containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Conditions for safe storage

Store in only approved and marked containers. Keep containers closed when not in use and during transportation. Keep containers away from flame or other ignition sources.

Incompatibilities

May react strong with oxidizing agents, such as hydrogen peroxide, bromine, and chromic acid.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy naphthenic	OSHA PEL (United States, 2/2013). TWA: 5 mg/m ³ 8 hours. ACGIH TLV (United States, 6/2013). TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 4/2013). TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist

Respiratory protection

If vapor mist is generated when the material is heated or handled, use approved respiratory protection. All respirators must be NIOSH certified. Fit testing may be required before use. Do not use compressed oxygen in hydrocarbon atmospheres. Adequate ventilation in accordance with good engineering practices must be provided to maintain concentrations below the specified exposure or flammable limits.

Hand protection

If handling hot material, use proper insulated gloves.

Eye protection

Not required under normal conditions of use. If material is handled such that it could be splashed or misted into eyes, wear plastic face shield or splash resistant safety goggles or glasses with side shields.

Skin and body protection

Use impervious clothing (boots, gloves, aprons, bibs, etc.) over parts of the body subject to exposure. If handling hot material, use insulated protective clothing. Contact your facility safety department or safety supplier to determine the proper protective equipment for your use.

Hygiene measures

Do not use contaminated clothing, launder clothing before reuse. Properly dispose of contaminated clothing or articles that cannot be laundered such as leather gloves, boots, etc. Wash contaminated areas of the body which may have been exposed with soap and water. Wash thoroughly before handling food and beverages. Food and beverage consumption should be avoided in work areas where hydrocarbons are present.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Semi-solid, emerald green

Physical state: Solid

Odor: Mineral Oil

Specific gravity (H₂O=1): 0.9560

Melting point/freezing point: No data available

Initial boiling point and boiling range: No data available

Flash point (C.O.C): >200°C, (392°F)

Upper/lower flammability or explosive limits: No data available

Vapor pressure: Not determined

Solubility in water: Negligible @25°C

Percent volatile: Negligible

Liquid density: Not determined

Evaporation rate: Not determined

10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions: Product will not undergo hazardous polymerization.

Conditions to avoid: Heat, open flames, oxidizing materials and mist.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: Carbon monoxide, carbon dioxide and other oxides may be generated as products of combustion.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity:

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Oral	Rat	>5000 mg/kg	-

Acute dermal toxicity:

Product/ingredient name	Result	Species	Score	Exposure	Observation
Distillates (petroleum), hydrotreated heavy naphthenic	Skin - Severe irritant	Rabbit	-	500 mg	-

12. ECOLOGICAL INFORMATION

Toxicity: There is no date available.

Persistence and degradability: There is no date available.

Bioaccumulative potential: There is no date available.

Mobility in soil:

Soil/water partition coefficient (K_{oc}): Not available.

Other adverse effects: No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

Waste Disposal methods

All disposals must comply with federal, state and local regulations. Spilled or discarded material may be a regulated waste. Refer to state and local regulations. If other material was used during cleanup efforts the resultant mixture may be regulated.

14. TRANSPORT INFORMATION

U.S. DOT Road/Rail/Waterways: Not dangerous/hazardous goods

Transport Canada Road/Rail/Waterways: Not dangerous/hazardous goods

15. REGULATORY INFORMATION

U.S. Federal regulations: **TSCA 8(a) CDR Exempt/Partial exemption:** All components are listed or exempted.
United States Inventory (TSCA 8b): All components are listed or exempted.

**Clean Air Act Section 112:
(b) Hazardous Air
Pollutants (HAPs)** Not listed

**Clean Air Act Section 602:
Class I Substances** Not listed

**Clean Air Act Section 602:
Class II Substances** Not listed

**DEA List I Chemicals:
(Precursor Chemicals)** Not listed

**DEA List II Chemicals:
(Essential Chemicals)** Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ: Not applicable

SARA 311/312

Classification: Not applicable

Composition/information on ingredients

No products were found.

State regulations:

Massachusetts: None of the components are listed.

New York: None of the components are listed.

New Jersey: The following components are listed: Distillates (petroleum), hydrotreated heavy naphthenic

Pennsylvania: None of the components are listed.

California Prop. 65:
No products were found.

NFPA Hazard Classification

Health: 0
Flammability: 1
Reactivity: 0



HMIS Classification

Health: 0
Flammability: 1
Physical Hazards: 0
Personal Protection: B

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate. However, neither Universal Lubricants, nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information provided herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

Rev. Date: 1/5/2017