



ECO ULTRA[®] SYNTHETIC BLEND ENGINE OILS

ECO ULTRA[®] Synthetic Blend Engine Oils are blended with highly re-refined Group II base oils and contain a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins. ECO ULTRA Synthetic Blend Engine Oils also protect engines from sludge, rust and acid build-up. These oils perform efficiently in gasoline engines and are outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 5W20</u>	<u>SAE 5W30</u>	<u>SAE 10W30</u>
Viscosity @ -30°C, cP	D5293	5000	6100	N/A
Viscosity @ -25°C, cP	D5293	N/A	N/A	5700
Viscosity @ 40°C, cSt	D445	46.00	64.00	68.00
Viscosity @ 100°C, cSt	D445	8.20	10.60	10.40
Viscosity Index	D2270	152	157	140
Flash Point, COC, °C	D92	229	231	231
Flash Point, COC, °F	D92	421	448	448
Pour Point, °C	D97	-40	-40	-36
Pour Point, °F	D97	-40	-40	-33
Color	D1500	3.0	3.0	2.5
Gravity, °API	D4052	32.8	32.6	29.5
HT/HS, cP	D4683	2.6	3.1	3.0

Meets or exceeds the following tests and requirements:

- API Service Classification - SN, ILSAC GF-5
- Chrysler MS-11999, MS-12007, MS-12015, MS-6395-S
- Resource Conserving
- Ford Motor Company - WSS-M2C945-A, WSS-M2C946-A
- Honda
- Toyota

NOTE: Certain tests apply to specific SAE grades.

EO-14/05.22.15