



## Full Synthetic Engine Oils

Medallion Plus® Full Synthetic Engine Oils are blended with the highest quality synthesized base stocks and contain a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins.

Medallion Plus Full Synthetic Engine Oils also protect engines from sludge, rust and acid build-up. These oils perform efficiently in gasoline engines and are outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

| <u>PROPERTY</u>        | <u>ASTM TEST METHOD</u> | <u>SAE 0W-20</u> | <u>SAE 5W-20</u> | <u>SAE 5W-30</u> | <u>SAE 10W-30</u> |
|------------------------|-------------------------|------------------|------------------|------------------|-------------------|
| Viscosity @ -35°C, cP  | D-5293                  | 6000             | N/A              | N/A              | N/A               |
| Viscosity @ -30°C, cP  | D-5293                  | N/A              | 4600             | 5800             | N/A               |
| Viscosity @ -25°C, cP  | D-5293                  | N/A              | N/A              | N/A              | 5800              |
| Viscosity @ 40°C, cSt  | D-445                   | 45.00            | 44.00            | 58.00            | 63.00             |
| Viscosity @ 100°C, cSt | D-445                   | 8.50             | 8.30             | 10.50            | 10.80             |
| Viscosity Index        | D-2270                  | 170              | 160              | 170              | 170               |
| Flash Point, COC, °C   | D-92                    | 213              | 213              | 213              | 213               |
| Flash Point, COC, °F   | D-92                    | 415              | 415              | 415              | 415               |
| Pour Point, °C         | D-97                    | -40              | -40              | -40              | -40               |
| Pour Point, °F         | D-97                    | -40              | -40              | -40              | -40               |
| Color                  | D-1500                  | 2.0              | 2.0              | 2.0              | 2.0               |
| Gravity, °API          | D-287                   | 36.0             | 35.5             | 36.0             | 36.0              |

Meets or exceeds the following tests and requirements:

- API Service Classification - SN, ILSAC GF-5
- Chrysler MS-11999, MS-12007, MS-12015, MS-6395-S
- Resource Conserving
- Ford Motor Company - WSS-M2C945A, WSS-M2C946A
- Honda/Toyota Genuine Oils

NOTE: Certain tests apply to specific SAE grades.