



---

## ECO ULTRA<sup>®</sup> FULL SYNTHETIC ENGINE OIL

ECO ULTRA<sup>®</sup> Full Synthetic Engine Oil is blended with the highest quality synthesized base stocks, high quality ECO ULTRA re-refined base stocks, and contains a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins. ECO ULTRA Full Synthetic Engine Oil also protects engines from sludge, rust and acid build-up. This oil performs efficiently in gasoline engines and is outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 0W20</u>
Viscosity @ -35°C, cP	D5293	6000
Viscosity @ -30°C, cP	D5293	N/A
Viscosity @ 40°C, cSt	D445	45.00
Viscosity @ 100°C, cSt	D445	8.50
Viscosity Index	D2270	160
Flash Point, COC, °C	D92	213
Flash Point, COC, °F	D92	415
Pour Point, °C	D97	-40
Pour Point, °F	D97	-40
Color	D1500	2.0
Gravity, °API	D287	32.0

Meets or exceeds the following tests and requirements:  
API Service Classification - SN, ILSAC GF-5  
Chrysler MS-11999, MS-12007, MS-12015, MS-6395-S  
Resource Conserving  
Honda/Toyota Genuine Oils

EO-21/05.22.15