



ECO ULTRA[®] HIGH MILEAGE ENGINE OILS

ECO ULTRA[®] High Mileage Engine Oils are blended with highly re-refined Group II base oils and contain a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins. ECO ULTRA High Mileage Engine Oils are formulated for older vehicles with greater than 75,000 miles to reduce leaks, condition seals and provide more film strength for better protection.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 5W20</u>	<u>SAE 5W30</u>	<u>SAE 10W30</u>
Viscosity @ -30°C, cP	D5293	6000	6300	N/A
Viscosity @ -25°C, cP	D5293	N/A	N/A	5700
Viscosity @ 40°C, cSt	D445	46.00	70.00	75.00
Viscosity @ 100°C, cSt	D445	8.20	11.30	11.50
Viscosity Index	D2270	152	160	145
Flash Point, COC, °C	D92	229	231	231
Flash Point, COC, °F	D92	421	448	448
Pour Point, °C	D97	-40	-40	-36
Pour Point, °F	D97	-40	-40	-33
Color	D1500	2.0	2.0	2.0
Gravity, °API	D4052	32.8	32.6	29.5
HT/HS, cP	D4683	2.6	3.1	3.0

Meets or exceeds the following tests and requirements:

API Service Classification - SN, ILSAC GF-5
Chrysler MS-11999, MS-12007, MS-12015, MS-6395-S
Resource Conserving
Ford Motor Company - WSS-M2C945-A, WSS-M2C946-A
Honda
Toyota

NOTE: Certain tests apply to specific SAE grades.

EO-25/05.22.15