



ECO ULTRA[®] SYNTHETIC BLEND dexos1[™] ENGINE OIL

Eco Ultra[®] Synthetic Blend dexos1[™] Engine Oil is blended with highly re-refined Group II base oils and contains a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins. Eco Ultra Synthetic Blend dexos1 Engine Oil also protects engines from sludge, rust and acid build-up. This oil performs efficiently in gasoline engines and is outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 5W30</u>
Viscosity @ -30°C, cP	D5293	6100
Viscosity @ -25°C, cP	D5293	N/A
Viscosity @ 40°C, cSt	D445	64.00
Viscosity @ 100°C, cSt	D445	10.60
Viscosity Index	D2270	157
Flash Point, COC, °C	D92	231
Flash Point, COC, °F	D92	448
Pour Point, °C	D97	-40
Pour Point, °F	D97	-40
Color	D1500	3.0
Gravity, °API	D4052	32.6
HT/HS, cP	D4683	3.1

Meets or exceeds the following tests and requirements:

- API Service Classification - SN, ILSAC GF-5
- Chrysler MS-11999, MS-6395-S
- Resource Conserving
- Ford Motor Company - WSS-M2C946-A
- Honda
- Toyota
- GM – dexos1 55573415, 6094M, 4718M

EO-27/05.22.15