



UNIVERSAL VINTAGE/CLASSIC PREMIUM SYNTHETIC ENGINE OIL

Universal Vintage/Classic Premium 5W-50 Engine Oil is a premium synthetic motor oil specially formulated for classic cars. The product has increased zinc levels to reduce metal-on-metal contact of aging engine parts. The high quality synthetic base oils combined with carefully selected, robust additives provide extra engine wear protection for older vehicles with flat tappet engines.

| <u>PROPERTY</u> | <u>ASTM TEST METHOD</u> | <u>SAE 5W50</u> |
|---------------------------|-----------------------------|---------------------|
| Viscosity @ -30°C, cP | D5293 | 6500 |
| Viscosity @ 40°C, cSt | D445 | 113.00 |
| Viscosity @ 100°C, cSt | D445 | 18.50 |
| Viscosity Index | D2270 | 185 |
| Flash Point, COC, °C (°F) | D92 | 220 (428) |
| Pour Point, °C (°F) | D97 | -45 (-49) |
| Color | D1500 | 3.0 |
| Gravity, °API | D287 | 34.0 |
| Sulfated Ash, % wt | D874 | 1.0 |
| Zinc, % | D4951 | 0.14 |
| Total Base Number (TBN) | D2896 | 10.5 |
| HT/HS, cP | D4683 | 3.80 |

Meets or exceeds the following tests and requirements:
API Service SN, SM, SL

EO-30/12.03.15