



## DYNA-PLEX 21C<sup>®</sup> SARGAS ENGINE OILS

Dyna-Plex 21C<sup>®</sup> Sargas Engine Oils are premium ashless lubricants for natural gas fueled engines. They are formulated from a 100% paraffin base oil containing a high performance, completely ashless additive package.

Dyna-Plex 21C Sargas Engine Oils provide outstanding deposit, wear and oil oxidation control in naturally aspirated and supercharged natural gas engines. Dyna-Plex 21C Sargas Engine Oils do not contribute to spark plug fouling, pre-ignition or port clogging tendencies, and permit trouble-free engine operation with minimum maintenance. Dyna-Plex 21C Sargas Engine Oils have proven effective under the most severe operating conditions in extensive field service.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 30</u>	<u>SAE 40</u>	<u>SAE 15W40</u>
Viscosity @ -20°C, cP	D5293	N/A	N/A	7000
Viscosity @ 40°C, cSt	D445	87.7	128.4	111.4
Viscosity @ 100°C, cSt	D445	10.4	13.5	15.1
Viscosity Index	D2270	100	97	140
Flash Point, COC, °C (°F)	D92	238 (460)	252 (485)	227 (440)
Pour Point, °C (°F)	D97	-12 (10)	-12 (10)	-34 (-30)
Color	D1500	2.5	3.0	2.5
Gravity, °API	D287	29.0	28.7	29.5
Sulfated Ash, % wt.	D874	Nil	Nil	Nil
Nitrogen, % wt.	D3228	0.06	0.06	0.06
Phosphorus, % wt.	D4951	0.05	0.05	0.05
Total Base Number (TBN)	D2896	1.2	1.2	1.2

NOTE: Check Engine Manufacturer's specifications before using any ashless gas engine oil. Ashless gas engine oils are not recommended for use in all LPG or natural gas engines.

EO-4/02.18.02