



---

## UNIVERSAL SUPER XHD ENGINE OILS

Universal Super XHD Engine Oils contain a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins. Universal Super XHD Engine Oils also protect engines from sludge, rust and acid build-up. These oils perform efficiently in gasoline engines and are outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 30</u>	<u>SAE 40</u>
Viscosity @ 40°C, cSt	D445	104.0	137.40
Viscosity @ 100°C, cSt	D445	11.90	14.40
Viscosity Index	D2270	101	103
Flash Point, COC, °C	D92	232	238
Flash Point, COC, °F	D92	450	460
Pour Point, °C	D97	-24	-18
Pour Point, °F	D97	-11	0
Color	D1500	2.5	2.5
Gravity, °API	D287	30.0	30.0
Sulfated Ash, %	D874	.98	.98
Phos., %	D4951	0.077	0.077
Zinc, %	D4951	0.085	0.085
Total Base No. (TBN)	D2896	7.4	7.4

Meets or exceeds the following tests and requirements:

- API Service Classification - SM
- Daimler Chrysler MS-6395-J, MS-9742, MS-9754, MS-9767
- Ford Motor Company - WSS-M2C153-G; WSS-M2C153-H
- General Motors - 9986187
- Military Specifications - CID-AA-52039

NOTE: Certain tests apply to specific SAE grades.

---

EO-7/10.25.04