



UNIVERSAL GL-5 SYNTHETIC GEAR OIL

Universal GL-5 Synthetic Gear Oil is formulated with synthetic base stocks for use in universal duty hypoid or spiral bevel gear differentials and manual transmissions in cars, light trucks and SUV's. It provides optimum axle and transmission protection and thermally stable extreme pressure agents protect against shock loading and wear.

Universal GL-5 Synthetic Gear Oil is fortified with anti-oxidants and corrosion inhibitors to resist damage from rust and oxidation.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 75W90</u>	<u>SAE 75W140</u>
Viscosity@40°C,cSt	D445	100.00	194.00
Viscosity@100°C,cSt	D445	14.50	25.00
Viscosity Index	D2270	160	160
Brookfield Viscosity@40°C,cP	D2983	115,000	125,000
Flash Point, COC, °C(°F)	D92	180 (356)	180
Pour Point, °C(°F)	D97	-36(-33)	-36
Color	D1500	2.0	2.0
Gravity, °API	D287	30.5	30.5
Copper Strip Corr. (250°F)	D130	1a	1a

Meets or exceeds the following tests and requirements:

- API Service Classification - GL-5
- Limited Slip Performance

GO-5/01.14.10