



DYNA-PLEX 21C[®] ALL SEASON TRACK ROLLER

Dyna-Plex 21C[®] All Season Track Roller is a semi-fluid grease. It is designed for use with the idler and track rollers on heavy duty construction equipment. It is also used as treatment for wire ropes and cables, is applicable as an open gear type grease, and use in centralized lube systems.

Dyna-Plex 21C All Season Track Roller has an NLGI rating of 0/00.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>NLGI #0 & #00</u>
Thickener Type		Lithium 12
Hydroxystearate		
Thickener Percent		1.85
Color		Reddish Brown
Texture		Smooth
Worked Penetration	D217	380-410
Dropping Point, °F	D2265	325
Rust Prevention	D1743	Perfect Pass
Oxidation Resistance @ 100 hrs	D942	-4 psi
Timken OK Load, lbs.	D2509	45
Approximate Temperature Range, °F		0 - 300
Base Oil/Additive Properties:		
Viscosity @ 100°C, cSt	D445	35.0
Viscosity @ 40°C, cSt	D445	450.0
Viscosity Index	D2270	117

NLGI #0 Worked Penetration 355-385
NLGI #00 Worked Penetration 400-430

GR-10/08.25.17