



DYNA-PLEX 21C[®] EP 620 MOLY SEMI-SYNTHETIC GREASE

Dyna-Plex 21C[®] EP 620 Moly Semi-Synthetic Grease is an aluminum complex grease specially formulated with both paraffinic base oils and synthetic base oils. It is enriched with molybdenum disulfide to provide added wear protection and to decrease friction.

Dyna-Plex 21C EP 620 Moly Semi-Synthetic Grease protects equipment that operates in extreme conditions, such as excessive heat, cold, pressure, shock loading, wet, and high or low speeds. It is a versatile grease that can be used in multiple applications.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	NLGI #1	NLGI #2	NLGI #3
Thickener Type		Aluminum Complex	Aluminum Complex	Aluminum Complex
Texture		Smooth, Tacky	Smooth, Tacky	Stiff, Tacky
Color		Black	Black	Black
Molybdenum Disulfide, %		5	5	5
Penetration				
60 Strokes	D217	310	295	240
10,000 Strokes	D217	325	280	232
Unworked	D217	320	305	245
Dropping Point, °C	D2265	246	264	274
Timken OK Load, lbs.	D2509	80	80	80
Four Ball EP				
Weld, kgs.	D2596	620	620	620
Base Oil/Additive Properties:				
Viscosity @ 40°C, cSt	D445	460	460	460
Viscosity Index	D2271	100	100	100

GR-6/06.08.04