



DYNA-PLEX 21C[®] HIGH PERFORMANCE HYDRAULIC OIL

Dyna-Plex 21C[®] High Performance Hydraulic Oil is specially formulated to meet the needs of heavy duty hydraulic systems. High quality ingredients include thermally stable antiwear agents, multifunctional ashless dispersants, rust and oxidation inhibitors, and anti-foam materials. This product offers excellent protection against wear, corrosion and rusting in hydraulic systems.

Dyna-Plex 21C High Performance Hydraulic Oil received a “pass” on the Vickers Vane Pump Test (35VQ25), is designed to resemble the new Caterpillar HYDO Advanced and contains > 900ppm zinc (0.09%) for CAT applications.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>10W</u>
Viscosity @-25°C, cP	D2602	4000
Viscosity @ 40°C, cSt	D445	42.00
Viscosity @ 100°C, cSt	D445	6.70
Viscosity Index	D2270	110
Flash Point, COC, °C (°F)	D92	216 (420)
Pour Point, °C (°F)	D97	-39 (-38)
Color	D1500	1.5
Gravity, °API	D287	31.5
Phosphorous, %	D4951	0.12
Zinc, %	D4951	0.14
FZG	D5182	12
SAE Crankcase Viscosity		10W
Vickers Vane Pump Test 35VQ25		Pass

HO-8/03.28.14