



Multi-Purpose Automatic Transmission Fluid

Medallion Plus® Multi-Purpose Automatic Transmission Fluid (ATF) provides the highest possible heat and oxidation protection for automatic transmissions of automobiles and light duty trucks. It is the one fluid you need for most applications, allowing you to reduce the number of products you need to inventory.

Medallion Plus Multi-Purpose ATF offers excellent low temperature performance and improved protection against high temperature deposits in heavy duty service. It has excellent corrosion and rust preventive properties, as well as rigid anti-foam characteristics. It will not cause excessive seal swell or shrinkage, nor will seals excessively harden or soften.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>TEST SPECIFICATIONS</u>
Viscosity @ 40°C, cSt	D-445	37.88
Viscosity @ 100°C, cSt	D-445	7.05
Viscosity Index	D-2270	180
Flash Point, COC, °C (°F)	D-92	204 (400)
Pour Point, °C (°F)	D-97	-43 (-45)
Color	D-1500	Red
Gravity, °API	D-287	32.0

GM 6137-M Tests:

Copper Strip Corrosion	No black
Anti-foaming Properties @ 93°C, mm	No foam
Anti-foaming Properties @ 135°C, mm	9.0
Rust Protection	No rust
Effect on Seals	Pass

Meets or exceeds the following tests and requirements:

General Motors – GM 6137-M, D-25196, D-21337, H-36166	Audi
Allison C-4, 30822004	Voith
Mercedes-Benz	ZF
Volkswagen	GMW
Volvo	Peugot

Can be used as an alternative with the following:

- Ford – ESP-M2C138-CJ, M2C166-H, M040612
- Caterpillar – TO-2
- Vickers Hydraulic Pump System
- Denison Hydraulic Pump System
- Sundstrand Hydraulic Pump System

Suitable for use in applicable pre-2006 GM and pre-2007 Ford automatic transmissions. Not recommended for transmissions requiring Ford Type F ATF.