



DYNA-PLEX 21C[®] SYNZOL TRANSMISSION OIL

Dyna-Plex 21C[®] Synzol Synthetic Manual Transmission Fluid is recommended for applications where heat and wear present major problems. These applications include manual transmissions where GL-1, GL-2, GL-3, and GL-4 type fluids are required.

Dyna-Plex 21C Synzol is a full synthetic designed for today's transmission synchronizers and is formulated for years of trouble-free shifting.

Dyna-Plex 21C Synzol meets Eaton and Meritor 750,000 mile extended warranty requirements, allowing the user to go 500,000 miles between drains in Eaton, Meritor, and Mack transmissions.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 50</u>
Viscosity @ -18°C, cP	D2602	N/A
Viscosity @ 40°C, cSt	D445	160
Viscosity @ 100°C, cSt	D445	18.60
Viscosity Index	D2270	133
Flash Point, COC, °C(°F)	D92	249(480)
Pour Point, °C(°F)	D97	-40(-40)
Color	D1500	Red
Gravity, °API	D287	23.0
Four Ball Wear - scar dia, mm.	D4172B	0.38
Copper Corrosion	D130	1b

Meets or exceeds the following tests and requirements:

- API GL-1, GL-2, GL-3, GL-4, MT-1
- Eaton Corporation - PS164 and PS081
- Mack - TO-A Plus
- Meritor 0-81
- International TMS-6816
- Volvo STD 97305

TO-7/02.14.07