



UNIVERSAL DEXRON® VI AUTOMATIC TRANSMISSION FLUID

Universal DEXRON® VI Automatic Transmission Fluid (ATF) is a next generation fluid approved for use in passenger car and light truck automatic transmissions that require a General Motors DEXRON VI or earlier generation DEXRON fluid. It is formulated to provide improved oxidation stability, shear stability, friction durability and foam resistance to help ensure long service life, better performance in extreme conditions and consistent shift performance for the life of the fluid.

Universal DEXRON VI ATF is particularly recommended for use in new GM 6-speed automatic transmissions, and is fully backwards compatible with older GM automatic transmissions. Universal DEXRON VI ATF is recommended for service fill in passenger cars and light trucks that require a GM DEXRON transmission fluid. It also may be used in industrial and mobile hydraulic systems operating over a wide temperature range.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>DATA</u>
Viscosity @ 40°C, cSt	D445	29.00
Viscosity @ 100°C, cSt	D445	5.95
Viscosity @ -40°C, cP	D2983	10,000
Viscosity Index	D2270	155
Flash Point, COC, °C (°F)	D92	216 (420)
Pour Point, °C (°F)	D97	-51 (-60)
Color	D1500	Red
Gravity, °API	D287	36.0
Zinc, ppm		<20
DEXRON VI Tests:		
Oxidation		Pass
Bench Tests		Pass
Band and Plate Friction		Pass
Elastomer Test		Pass

Meets or exceeds the following tests and requirements:
General Motors - DEXRON VI
GM License Number - J-60157

Suitable for use in all applicable GM automatic transmissions.

Not recommended for transmissions requiring MERCON or Ford Type F ATF.

TO-8/09.27.07